High-performance scalable server

For Compute-Intensive Workloads

For medium to large enterprises, and managed and cloud service providers, Lenovo ThinkSystem SR650 is the optimum 2U, two-socket server-the most widely used server type worldwide. It's engineered to deliver high performance with 205W CPUs, low-latency NVMe drives, and high-power GPUs.

With Lenovo's history of reliability, the highly flexible and configurable SR650 is the ideal platform for hyperconverged infrastructure (HCI) or software-defined storage (SDS). It provides a solid foundation for: 1) transforming physical resources into services, using validated designs for hybrid cloud; 2) performing analytics on streaming data, using validated designs for Big Data; and 3) increasing productivity of virtualized transactional systems, using validated designs for OLTP databases.

Versatile and Scalable

ThinkSystem SR650 incorporates up to two powerful Intel® Xeon® processor Scalable family CPUs, with 27 percent more cores and twice the memory capacity of the previous generation server*. It supports two 300W high-performance GPUs and ML2 NIC adapters with shared management. Unique Lenovo AnyBay technology provides the flexibility to mix-and-match SAS/SATA HDDs/SSDs and NVMe SSDs in the same drive bays. Four direct-connect NVMe ports on the motherboard provide ultra-fast read/writes with NVMe drives and reduce costs by eliminating PCIe switch adapters. Plus, storage can be tiered for greater application performance, to provide the most cost-effective solution. Optional mirrored M.2 drives ensure reliability and guick OS initialization. SR650 also features 80 PLUS Platinum and Titanium PSUs, as well as continuous operation at 45°C, to reduce energy costs.

Easily Managed

Lenovo XClarity Controller is an all-new hardware embedded management engine common in every ThinkSystem server. XClarity Controller features an uncluttered graphical user interface, industry standard Redfish-compliant REST APIs, and enables booting in half the time of prior generation servers, with up to 6x faster firmware updates.

Lenovo XClarity Administrator is a virtualized application that centrally manages ThinkSystem servers, storage, and networking. Via reusable patterns and policies, it ramps up and scales infrastructure provisioning and maintenance. It serves as a central integration point to extend your data center management processes to physical IT. Running XClarity Integrators in external IT applications, or integrating through REST APIs, helps you further speed services provisioning, streamline IT management, and contain costs.

Lenovo servers continue to be the industry's #1 most reliable⁺, with the industry's highest customer satisfaction^t rating.

Why Lenovo

Lenovo is the leading provider of x86 systems for the data center. The portfolio includes rack, tower, blade, dense and converged systems, and supports enterprise class performance, reliability and security. Lenovo also offers a full range of networking, storage, software and solutions, and comprehensive services supporting business needs throughout the IT lifecycle.







Lenovo ThinkSystem SR650



Specifications

2U rack server	
Up to 2x Intel® Xeon® Platinum processors, up to 205W	
Up to 3TB [®] in 24x DIMM slots using 128GB DIMMs; 2666MHz TruDDR4	
Up to 7x PCIe 3.0 via multiple riser options, including 1x dedicated PCIe slot for RAID adapter	
Up to 24 HS bays (incl. 4 or 8 AnyBay): plus up to 2x mirrored M.2 boot (opt. RAID 1)	
Hardware RAID (up to 24 ports) with flash cache; up to 16-port HBAs	
TPM 1.2/2.0; PFA; HS/redundant drives, fans, and PSUs; 45°C continuous operation; light path diagnostic LEDs; front-access diagnostics via dedicated USB port	
2/4-port 1GbE LOM; 2/4-port 10GbE LOM (Base-T or SFP+); 1x dedicated 1GbE mngmt port	
2x hot swap/redundant: 550W/750W/1100W/1600W 80 PLUS Platinum; or 750W 80 PLUS Titanium	
XClarity Controller embedded management, XClarity Administrator centralized infrastructure delivery, XClarity Integrator plugins, and XClarity Energy Manager centralized server power management	
Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware vSphere. Visit lenovopress.com/osig for details.	
1- and 3-year customer replaceable unit and onsite service, next business day 9x5; opt. service upgrades	

* Compared to Lenovo x3650 M5.; * 2016-2017 Global Hardware, Server OS Reliability Report, ITIC; October 2016.

¹ 2H16 Corporate IT Buying Behavior and Customer Satisfaction Study, TBR; December 2016.; ^a 1.5TB at GA; 128GB DIMMs available in the near future. Available prior to GA via special bid.

Featured Options

NVIDIA Tesla P100 16GB PCIe Passive GPU	Intel OPA 100 Series Single-port PCIe 3.0 x16 HFA	2.5-inch 7.68TB SAS 12Gb Hot-Swap SSD
7X67A00068	00WE027	7N47A00122
Designed to boost throughput for HPC and hyperscale data centers	Designed for HPC workloads with low end-to-end latency	High-performance/reliability solution for read/capacity-intensive applications

Visit Options for more information.

For More Information

To learn more about the Lenovo ThinkSystem SR650, contact your Lenovo representative or Business Partner or visit www.lenovo.com/thinksystem. For detailed specs, consult the SR650 Product Guide.

NEED STORAGE?	Learn more about Lenovo Storage www.lenovo.com/systems/storage
NEED SERVICES?	Learn more about Lenovo Services

© 2017 Lenovo. All rights reserved.

Availability: Offers, prices, specifications and availability may change without notice. Lenovo is not responsible for photographic or typographical errors. Warranty: For a copy of applicable warranties, write to: Lenovo Warranty Information, 1009 Think Place, Morrisville, NC, 27560. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, AnyBay, ThinkSystem, and XClarity are trademarks or registered trademarks of Lenovo. Microsoft and Windows are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Xeon and Xeon Inside are registered trademarks of Intel Corporation in the U.S. and other countries. Other company, product, and service names may be trademarks or service marks of others.

