

Product datasheet

Specifications



APC Back-UPS Pro for Gaming,
2200VA/1320W, Tower, 230V, 6x
Australian outlets, RGB Lights,
Pure Sine Wave, Midnight (Black)

BGM2200B-AZ

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V AC 1 phase
Other Input Voltage	230 V
Main Output Voltage	230 V 1 phase
Rated power in W	1320 W
Rated power in VA	2200 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	Australian
output connection type	3 Australian 3 Australian surge
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Overcurrent protection	15 A
Battery charger power	12 W rated
Battery life	3...5 year(s)

General

Provided equipment	safety guide USB cable power cable
product web sub-family	Gaming performance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number preinstalled power module	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	292.1 mm
Width	104.1 mm
Depth	408.9 mm
Net weight	12.56 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

Input

Network frequency	50/60 Hz +/- 3 Hz
Plug standard	Australian
Input voltage limits	168...302 V
Maximum input current	12 A
Switching current capacity	15 A
Input harmonic distortion	Less than 3 % for full load
Input protection type	Circuit breaker

Output

Maximum configurable power in W	1320 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Full load runtime	00:30:00
Half load runtime	00:05:30
Maximum configurable power in VA	2200 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...3048.0000000000 m
Acoustic level	45 dBA
IP degree of protection	IP20

Communications & Management

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	35.5 cm
Package 1 Length	48 cm
Package 1 Weight	14.38 kg

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performances. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

 Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information